



Car Top Duffle Bag Set Up Guide

The correct attachment of this product is critical and beyond the control of Rightline Gear. The safe use and long life of this product depends entirely on your good judgment and following these directions.

Pack The Car Top Duffle Bag

- 1-Pack the Duffle Bag full, close the zipper, and secure the Velcro-close zipper cover.
- 2-Place items with sharp or pointed edges in the middle and pack softer items around them.
- 3-Remove the handle straps of the Duffle Bag and place them in the outer pocket.
- 4-Place the Duffle Bag(s) on the vehicle's roof in one of the following configurations:
 - (1) Duffle Bag - in center of roof - requires (1) strap set
 - (2) Duffle Bags - side by side - requires (1) strap set
 - (3) Duffle Bags - (2) side by side in front, (1) in center of roof in rear - requires (2) strap sets
 - (4) Duffle Bags - (2) side by side in front, (2) side by side in rear - requires (2) strap sets

The Car Top Duffle Bag straps can be used to attach the bag(s) to vehicles WITH or WITHOUT a roof rack.

WARNING: DO NOT ATTACH STRAPS DIRECTLY TO THE D-RINGS; DAMAGE MAY RESULT. THE D-RINGS FUNCTION AS GUIDES FOR THE STRAPS, NOT AS ATTACHMENT POINTS FOR THE STRAPS.

Attach The Car Top Duffle Bag - WITH A Roof Rack

The Car Top Duffle Bag comes with (2) straps that attach side to side between the roof rack side rails (after you remove the Car Clips). Make sure the roof rack is anchored to your vehicle and don't exceed its weight limit.

1-Unthread the short strap piece from the center buckle on the first strap (Fig 1).

2-Attach the short strap piece to your rack by threading its end through its loop and pulling tight (Fig 2). Go to the opposite side of the vehicle and secure the long piece to the rack by the same method.



3-Run both strap pieces through the side d-rings of the outermost Duffle Bag(s) (Fig 3 and Fig 4). Run the long strap piece through the top d-ring(s) (Fig 3 and Fig 5). Make sure the center buckle is facing up and the strap pieces are not twisted.



4-Thread the short strap piece back through the center buckle and tighten (Fig 6).



5-Repeat steps 1-4 for the second strap (Fig 7).

Attach The Car Top Duffle Bag - WITHOUT A Roof Rack

On a 4-door vehicle, (1) strap will attach to the front door frames and (1) strap will attach to the rear door frames. On a 2-door vehicle, (2) straps will attach to the front door frames.

1-Unthread the short strap piece from the center buckle on the first strap (Fig 8).



Fig 8

2-Run both strap pieces through the side d-rings of the outermost Duffle Bag(s) (Fig 9 and Fig 10). Run the long strap piece through the top d-ring(s) of the Duffle Bag(s) (Fig 9 and Fig 11). Make sure the center buckle is facing up and the strap pieces are not twisted.



Fig 9



Fig 10



Fig 11

3-Thread the short strap piece back through the center buckle (Fig 12).



Fig 12

4-Attach the Car Clips under the door frame weather molding and tighten the strap (Fig 13). Make sure the strap has enough tension to keep the top of the Clips straight up and down (not angling out from the door frame).



Fig 13



Fig 14

5-Repeat steps 1-4 for the second strap (Fig 14).

6-Shut the vehicle's doors over the clips/straps (Fig 15).



Fig 15

Final Adjustments For All Straps



Fig 16

Fig 17

1-Move each strap's tri-glide to the end of the loose strap (Fig 16).

2-Tie off any excess strap on the other side of the center buckle (Fig 17). If the straps are too long, cut off the extra length and melt the cut end to prevent fraying.

3-Check the straps before driving and regularly throughout the trip.

www.rightlinegear.com

LIMITED WARRANTY

Rightline Gear warrants that for one (1) year, from the date of purchase that all products will be free of material defect and Rightline Gear will repair or replace any defective or damaged product free of charge if it is returned in original condition by the consumer to Rightline Gear or the place of purchase. Claims of defective material and/or workmanship must be made in a timely manner. Safe and maintenance-free use of this product depends upon the consumer's or user's proper installation of the product and good judgment in its use. Rightline Gear is not responsible for the consumer's or user's use or misuse of this product. Damage to Purchaser's vehicle or any other vehicle caused by Purchaser's improper use of this product may cause serious injury or death. The Purchaser acknowledges that Rightline Gear has no control over the attachment of its products to vehicles or the attachment of items to the Rightline Gear products. Accordingly, Rightline Gear cannot assume responsibility for any damage to any property arising out of the improper attachment or use of its products.

RIGHTLINE GEAR SPECIFICALLY DISCLAIMS ANY AND ALL OTHER WARRANTIES WHETHER EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO WARRANTY OF MERCHANTABILITY AND WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE. RIGHTLINE GEAR FURTHER DISCLAIMS ANY WARRANTY OR OTHER PROMISE THAT GIVES RISE TO ANY SORT OF CONSEQUENTIAL, EXTRAORDINARY, PUNITIVE, EXEMPLARY, SUBSEQUENT, OR NONECONOMIC DAMAGES OR ATTORNEY FEES. THE CONSUMER OR USER'S SOLE REMEDY AGAINST RIGHTLINE GEAR FOR ANY DEFECT IN THIS PRODUCT IS LIMITED TO FULL RETURN OF THE PURCHASE PRICE.

RIGHTLINE GEAR SPECIFICALLY ENCOURAGES COMPLIANCE WITH ALL MOTOR VEHICLE LAWS, AND EXPRESSLY DISCLAIMS ANY AND ALL LIABILITY FOR FAILURE TO COMPLY WITH SAME.